

GAS N-Series

Specifications

	NPR Gas	NPR Gas Crew Cab	NPR-HD Gas	NPR-HD Gas Crew Cab
GVWR/GCWR	12,000/18,000 lbs. .	12,000/18,000 lbs.	14,500/20,500 lbs.	14,500/20,500 lbs.
BODY/PAYLOAD ALLOWANCE	6,782-6,978 lbs.	6,246-6,308 lbs.	8,977-9,174 lbs.	8,442-8,503 lbs.
GAWR				
<i>Front</i>	4,860 lbs.	4,860 lbs.	6,630 lbs.	6,630 lbs.
<i>Rear</i>	8,840 lbs.	8,840 lbs.	11,020 lbs.	11,020 lbs.
FRONT AXLE CAPACITY	6,830 lbs.	6,830 lbs.	6,830 lbs.	6,830 lbs.
REAR AXLE CAPACITY	11,020 lbs.	11,020 lbs.	11,020 lbs.	11,020 lbs.
<i>Ratio</i>	5.125	5.125	5.375	5.375
SUSPENSION F/R SPRINGS	Tapered/Multi-Leaf	Tapered/Multi-Leaf	Tapered/Multi-Leaf	Tapered/Multi-Leaf
<i>Capacity</i>	8,440/12,900 lbs.	8,440/12,900 lbs.	8,440/12,900 lbs.	8,440/12,900 lbs.
FRAME				
<i>Section Modulus</i>	7.20 in. ³	7.20 in. ³	7.20 in. ³	7.20 in. ³
<i>Resistance Bending Moment</i>	316,800 lb.-ft./in.	316,800 lb.-ft./in.	316,800 lb.-ft./in.	316,800 lb.-ft./in.
SERVICE BRAKES	Vacuum/Hydraulic with	Vacuum/Hydraulic with	Vacuum/Hydraulic with	Vacuum/Hydraulic with
<i>Front/Rear</i>	4-Channel ABS Disc/Drum	4-Channel ABS Disc/Drum	4-Channel ABS Disc/Drum	4-Channel ABS Disc/Drum
TRANSMISSION	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter	6L90 6-speed auto. with double overdrive and lock-up converter
ENGINE	GMPT L96 (Gen IV)V8 Vortec 6000 (Optional: KL8-Alternative Fuel Capable Engine)	GMPT L96 (Gen IV)V8 Vortec 6000 (Optional: KL8-Alternative Fuel Capable Engine)	GMPT L96 (Gen IV)V8 Vortec 6000 (Optional: KL8-Alternative Fuel Capable Engine)	GMPT L96 (Gen IV)V8 Vortec 6000 (Optional: KL8-Alternative Fuel Capable Engine)
<i>Displacement</i>	6.0L (365 in. ³)	6.0L (365 in. ³)	6.0L (365 in. ³)	6.0L (365 in. ³)
<i>Engine Power</i>	297hp @ 4,300 rpm	297hp @ 4,300 rpm	297hp @ 4,300 rpm	297hp @ 4,300 rpm
<i>Engine Torque</i>	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm	372 lb.-ft. @ 4,000 rpm
LIMITED SLIP DIFFERENTIAL	Optional	Optional	Optional	Optional
ALTERNATOR	145-amp	145-amp	145-amp	145-amp
BATTERIES	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA	1 Maintenance-Free 750-CCA
TIRES LRR (Low Rolling Resistance)	215/85R16E (10-pr) Standard	215/85R16E (10-pr) Standard	225/70R19.5G (14-pr) Standard	225/70R19.5G (14-pr) Standard
STEERING	Integral Hydraulic Power	Integral Hydraulic Power	Integral Hydraulic Power	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic	Tilt and Telescopic	Tilt and Telescopic	Tilt and Telescopic
FUEL TANK	30 gal. in-frame	30 gal. in-frame	30 gal. in-frame	30 gal. in-frame

