

Power Your Business with the Isuzu NPR Class 3 Diesel LCF

- Class leading payload 7,435 - 7,607 lbs.
- An easy to drive low cab forward medium duty truck with outstanding driver visibility, maneuverability and a tight turning radius
- A spacious cab with seating for three that provides maximum driver efficiency and comfort
- 3.0L 150 hp diesel engine with class-leading fuel economy, B20 biodiesel capability and a B-10 service life of 310,000 miles
- A straight rail industry-standard chassis that permits maximum vocational body upfit capability to cargo space with flat body floors and body length options up to 20 ft
- Add a class 3 work truck to your business with legendary dependability, vehicle service and support programs, a lower cost of ownership and remarkable lifecycle value



CLASS
LEADING
PAYLOAD

**CLASS
LEADING
PAYLOAD**

STANDARD CAB

GVWR/GCWR	13,000/19,000 lbs.
BODY/PAYLOAD ALLOWANCE	7,435 - 7,607 lbs.
GAWR	
Front	5,360 lbs.
Rear	9,880 lbs.
FRONT AXLE CAPACITY	6,830 lbs.
REAR AXLE CAPACITY	11,020 lbs.
Ratio	5.125
SUSPENSION F/R SPRINGS	Tapered/Multi-Leaf
Capacity	6,830/9,880 lbs.
FRAME	
Section Modulus	7.20 in. ³
Resistance Bending Moment	316,800 lb.-ft./in.
SERVICE BRAKES	Vacuum/Hydraulic with
Front/Rear	4-Channel ABS Disc/Drum
EXHAUST BRAKE	Standard
TRANSMISSION	Aisin A460 6-speed auto. with double overdrive and lock-up 2 nd -6 th gears
ENGINE	
Isuzu 4JJ1-TC turbocharged intercooled diesel	
Displacement	3.0L (183 in. ³)
Engine Power	150hp @ 2,800 rpm
Engine Torque	282 lb.-ft. @ 1,600-2,800 rpm
Oil Level Indicator	Dash-mounted oil level check switch and light
LIMITED SLIP DIFFERENTIAL	Optional
ALTERNATOR	140-amp
BATTERIES	2 Maintenance-Free 750-CCA
TIRES LRR (Low Rolling Resistance)	215/85R16E (10-pr) Standard
STEERING	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic
FUEL TANK	30 Gal. in-rail
FUEL/WATER SEPARATOR	Dual fuel filter with dash mounted indicator light

DIESEL 13,000 LBS

GVWR

NPR

ISUZU
TRUCK

Large main mirror and integral adjustable convex mirror

3.0L 150HP diesel with class-leading fuel economy, B20 biodiesel capable

Aisin A460 6-speed double overdrive transmission - PTO capable

Body lengths up to 20 feet

Class leading payload 7,435 - 7,607 lbs.

Exhaust brake (standard)

Bodies up to 102" wide

Clean top of frame for variety of body applications

Up to 91" body height

Wheel cut angle 49.5°

Four wheelbases:

- 109"
- 132.5"
- 150"
- 176"

Low Rolling Resistance (LRR), steel belted, all season tires in all positions

30 gallon fuel tank

33.5" industry standard frame width

