

FTR | 25,950 LBS. GVWR CLASS 6



2023 ISUZU F-SERIES

GVWR/GCWR	25,950/30,000 lbs.
BODY/PAYLOAD ALLOWANCE	14,505-16,264 lbs.
GAWR	
Front Standard	12,000 lbs.
Front Low Pro	11,000 lbs.
Rear	19,000 lbs.
FRONT AXLE CAPACITY	12,000 lbs.
REAR AXLE CAPACITY	19,000 lbs.
FINAL RATIO	5.57 4.88 (Low Pro)
SUSPENSION F/R SPRINGS	Tapered Leaf/Multi-Leaf
Capacity	12,000/21,000 lbs.
AIR SUSPENSION F/R SPRINGS	Tapered Leaf/HAS 230 Air
Capacity	12,000/23,000 lbs.
FRAME	
Section Modulus	12.69 in. ^{^3}
Resistance Bending Moment	1,015,000 lb.-in.
SERVICE BRAKES	Full Air Dual Circuit with ABS
Front/Rear	S-CAM Drum Automatic Adjust
EXHAUST BRAKES	Standard
TRANSMISSION	Allison® 2550 RDS 6-Speed Automatic (Includes Park Pawl)
ENGINE	Cummins B6.7 Turbocharged Intercooled Diesel
Displacement	6.7L (408 in. ^{^3})
Engine Power	260hp @ 2,400 RPM
Engine Torque	660 lb.-ft. @ 1,600 rpm
ALTERNATOR	160-amp
BATTERIES	2 Maintenance-Free Group 31 750-CCA
TIRES LLR (Low Rolling Resistance)	11R22.5G (14-pr) Standard
Low Pro	255/70R22.5H (16-pr) Standard Low Pro
STEERING	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic
FUEL TANK	50 or 100 Gal. LH Side Mount
FUEL/WATER SEPARATOR	Dual Filter with Dash Mounted Indicator Light

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
152	127.0	192.9	10.4	274.4	14-16
170	145.0	220.0	10.4	301.5	18
188	163.0	247.0	10.4	328.5	20
200	175.0	264.9	10.4	346.4	22
212	187.0	283.1	10.4	364.6	24
224	199.0	301.0	10.4	382.5	26
236	211.0	319.1	10.4	400.6	28
248	223.0	337.0	10.4	418.5	30

