

FVR | 25,950 LBS. GVWR CLASS 6

Derate



GVWR/GCWR 25,950/33,000 lbs.

BODY/PAYLOAD ALLOWANCE 14,405-15,939 lbs.

GAWR
Front 12,000 lbs.
Rear 21,000 lbs.

FRONT AXLE CAPACITY 12,000 lbs.

REAR AXLE CAPACITY 21,000 lbs.

FINAL RATIO 5.57

SUSPENSION F/R SPRINGS
Capacity Tapered Leaf/Multi-Leaf
12,000/21,000 lbs.

AIR SUSPENSION F/R SPRINGS
Capacity Tapered Leaf/HAS 230 Air
12,000/23,000 lbs.

FRAME
Section Modulus 12.69 in.³
Resistance Bending Moment 1,015,000 lb.-in.

SERVICE BRAKES
Front/Rear Full Air Dual Circuit with ABS
S-CAM Drum Automatic Adjust

EXHAUST BRAKES Standard

TRANSMISSION Allison® 2500 RDS 6-Speed Automatic
(Park Pawl N/A)

ENGINE
Displacement Cummins B6.7 Turbocharged Intercooled
Diesel 6.7L (408 in.³)
Engine Power 260hp @ 2,400 RPM
Engine Torque 660 lb.-ft. @ 1,600 rpm

ALTERNATOR 160-amp

BATTERIES 2 Maintenance-Free
Group 31 750-CCA

TIRES LLR (Low Rolling Resistance) 11R22.5G (14-pr) Standard

STEERING Integral Hydraulic Power

STEERING COLUMN Tilt and Telescopic

FUEL TANK 50 or 100 Gal. LH Side Mount

FUEL/WATER SEPARATOR Dual Filter with Dash Mounted Indicator
Light

2023 ISUZU F-SERIES

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
152	127.0	192.9	10.4	274.4	14-16
170	145.0	220.0	10.4	301.5	18
188	163.0	247.0	10.4	328.5	20
200	175.0	264.9	10.4	346.4	22
212	187.0	283.1	10.4	364.6	24
224	199.0	301.0	10.4	382.5	26
236	211.0	319.1	10.4	400.6	28
248	223.0	337.0	10.4	418.5	30

