

NPR-HD

14,500 LBS. GVWR
CLASS 4



GVWR/GCWR	14,500/20,500 lbs.
BODY/PAYLOAD ALLOWANCE	7,545-8,511 lbs.
GAWR	
Front	5,360 lbs.
Rear	9,880 lbs.
FRONT AXLE CAPACITY	6,830 lbs.
REAR AXLE CAPACITY	11,020 lbs.
Ratio	4.555
SUSPENSION F/R SPRINGS	Tapered/Multi-Leaf
Capacity	6,830/9,880 lbs.
SERVICE BRAKES	Vacuum/Hydraulic with
Front/Rear	4-Channel ABS Disc Brakes
EXHAUST BRAKE	Standard
TRANSMISSION	Aisin A465id 6-speed auto with double overdrive and lock-up 2 nd -6 th gears

ENGINE	Isuzu 4HK1-TC turbocharged intercooled diesel
Displacement	5.2L (317 in. ³)
Engine Power	215hp @ 2,500 rpm
Engine Torque	452 lb.-ft. @ 1,850 rpm
OIL LEVEL INDICATOR	Dash-mounted oil level check switch and light
ALTERNATOR	140-amp
BATTERIES	2 Maintenance-Free Group 31 750-CCA
TIRES LRR (Low Rolling Resistance)	215/85R16E (10-pr) Standard
STEERING	Integral Hydraulic Power
STEERING COLUMN	Tilt and Telescopic
FUEL TANK Standard Optional	30 Gal. in-rail stainless steel 35 Gal. aluminum LH side mount (150 & 176" WB Only) 55 Gal. aluminum LH side mount (176" WB Only)
FUEL TANK	Dual fuel filter with dash mounted indicator light

2023 ISUZU N-SERIES

STANDARD CAB

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
109.0	86.5	129.6	7.7	200.5	10-12
132.5	110.0	153.1	7.7	224.0	12-14
150.0	127.5	170.6	7.7	241.5	16-18
176.0	153.5	196.6	7.7	267.5	18-20

CREW CAB

150.0	88.5	131.6	5.3	241.5	12
176.0	114.5	157.6	5.3	267.5	16

