

# NPR-XD

16,000 LBS. GVWR  
CLASS 4



|                               |  |
|-------------------------------|--|
| <b>GVWR/GCWR</b>              | 16,000/22,000 lbs.   |
| <b>BODY/PAYLOAD ALLOWANCE</b> | 8,639-9,605 lbs.   |
| <b>GAWR</b>                   |  |
| Front                         | 6,630 lbs.   |
| Rear                          | 11,020 lbs.  |
| <b>FRONT AXLE CAPACITY</b>    | 6,830 lbs.   |
| <b>REAR AXLE CAPACITY</b>     | 11,020 lbs.  |
| Ratio                         | 4.777  |
| <b>SUSPENSION F/R SPRINGS</b> | Tapered/Multi-Leaf   |
| Capacity                      | 8,440/14,308 lbs.  |
| <b>SERVICE BRAKES</b>         | Vacuum/Hydraulic with  |
| Front/Rear                    | 4-Channel ABS Disc Brakes  |
| <b>EXHAUST BRAKE</b>          | Standard   |
| <b>TRANSMISSION</b>           | Aisin A465id 6-speed auto<br>with double overdrive and<br>lock-up 2 <sup>nd</sup> -6 <sup>th</sup> gears |

|  |   |
|--|---|
| <b>ENGINE</b>                                | Isuzu 4HK1-TC turbocharged<br>intercooled diesel  |
| Displacement                                 | 5.2L (317 in. <sup>3</sup> )  |
| Engine Power                                 | 215hp @ 2,500 rpm   |
| Engine Torque                                | 452 lb.-ft. @ 1,850 rpm   |
| <b>OIL LEVEL INDICATOR</b>                   | Dash-mounted oil level check switch<br>and light  |
| <b>ALTERNATOR</b>                            | 140-amp   |
| <b>BATTERIES</b>                             | 2 Maintenance-Free<br>Group 31 750-CCA  |
| <b>TIRES LRR</b><br>(Low Rolling Resistance) | 225/70R19.5F (12-pr)<br>Standard  |
| <b>STEERING</b>                              | Integral Hydraulic Power  |
| <b>STEERING COLUMN</b>                       | Tilt and Telescopic   |
| <b>FUEL TANK</b><br>Standard<br>Optional     | 30 Gal. in-rail stainless steel<br>35 Gal. aluminum LH side mount<br>(150 & 176" WB Only)<br>55 Gal. aluminum LH side mount<br>(176" WB Only) |
| <b>FUEL TANK</b>                             | Dual fuel filter with dash mounted<br>indicator light   |

## 2023 ISUZU N-SERIES

### STANDARD CAB

| Wheelbase (in.) | Cab to Axle (in.) | Cab to End of Frame (in.) | Back of Cab (in.) | Overall Length (in.) | Body Length (ft.) |
|-----------------|-------------------|---------------------------|-------------------|----------------------|-------------------|
| 109.0           | 86.5              | 129.6                     | 7.7               | 200.5                | 10-12             |
| 132.5           | 110.0             | 153.1                     | 7.7               | 224.0                | 12-14             |
| 150.0           | 127.5             | 170.6                     | 7.7               | 241.5                | 16-18             |
| 176.0           | 153.5             | 196.6                     | 7.7               | 267.5                | 18-20             |

### CREW CAB

|       |       |       |     |       |    |
|-------|-------|-------|-----|-------|----|
| 150.0 | 88.5  | 131.6 | 5.3 | 241.5 | 12 |
| 176.0 | 114.5 | 157.6 | 5.3 | 267.5 | 16 |

