

NQR

17,950 LBS. GVWR CLASS 5



2023 ISUZU N-SERIES

STANDARD CAB

Wheelbase (in.)	Cab to Axle (in.)	Cab to End of Frame (in.)	Back of Cab (in.)	Overall Length (in.)	Body Length (ft.)
109.0	86.5	129.6	7.7	200.5	10-12
132.5	110.0	153.1	7.7	224.0	12-14
150.0	127.5	170.6	7.7	241.5	16-18
176.0	153.5	196.6	7.7	267.5	18-20
200.0	177.5	220.6	7.7	291.5	22

CREW CAB

150.0	88.5	131.6	5.3	241.5	12
176.0	114.5	157.6	5.3	267.5	16

- GVWR/GCWR** 17,950/23,950 lbs.
- BODY/PAYLOAD ALLOWANCE** 10,485-11,463 lbs.
- GAWR**
Front 6,830 lbs.
Rear 12,980 lbs.
- FRONT AXLE CAPACITY** 6,830 lbs.
- REAR AXLE CAPACITY** 14,550 lbs.
Ratio 5.125
- SUSPENSION F/R SPRINGS** Tapered/Multi-Leaf
Capacity 8,440/14,550 lbs.
- SERVICE BRAKES** Vacuum/Hydraulic with
Front/Rear 4-Channel ABS Disc Brakes
- EXHAUST BRAKE** Standard
- TRANSMISSION** Aisin A465id 6-speed auto
with double overdrive and
lock-up 2nd-6th gears
- ENGINE** Isuzu 4HK1-TC turbocharged
intercooled diesel
Displacement 5.2L (317 in.³)
Engine Power 215hp @ 2,500 rpm
Engine Torque 452 lb.-ft. @ 1,850 rpm
- OIL LEVEL INDICATOR** Dash-mounted oil level check switch
and light
- ALTERNATOR** 140-amp
- BATTERIES** 2 Maintenance-Free
Group 31 750-CCA
- TIRES LRR** 225/70R19.5F (12-pr)
(Low Rolling Resistance) Standard
- STEERING** Integral Hydraulic Power
- STEERING COLUMN** Tilt and Telescopic
- FUEL TANK** 30 Gal. in-rail stainless steel
Standard
Optional 35 Gal. aluminum LH side mount
(150 & 176" WB Only)
55 Gal. aluminum LH side mount
(176" WB Only)
- FUEL TANK** Dual fuel filter with dash mounted
indicator light

